

EdgeGuard ™

Living roof systems

Application

- Designed for use in variety of green or ballasted roof applications
- Can be used either as an edge restraint, or where a solution for retaining or separating the roof garden materials is required.

Key Features


- Supplied in 2.4 M lengths quick installation
- Lightweight and robust, can be cut to length
- Available powder coated in any colour
- Unique connection system
- Can be angled to suit the roof design

Datasheet

04 ROOFTOP PRODUCTS EdgeGuard™ Living roof systems


EdgeGuard™ Living roof systems

code	Description	Height (mm)	Width of base (mm)	Material thickness (mm)	Length of section (mm)
EG-A-50/2400	Aluminium, pre-punched and profiled	50	100	1.5	2400
EG-A-75/2400		75	100	1.5	
EG-A-100/2400		100	100	1.5	
EG-A-120/2400		120	100	1.5	
EG-A-150/2400		150	150	1.5	
EG-A-200/2400		200	150	2.0	
EG-A-250/2400		250	200	2.0	
EG-A-300/2400		300	200	2.0	



EG-A

code	Description	Height (mm)	Width of base (mm)	Material thickness (mm)	Length of section (mm)
EG-F-50/2400	Aluminium, pre-punched and profiled	50	100	1.5	2400
EG-F-75/2400		75	100	1.5	
EG-F-100/2400		100	100	1.5	
EG-F-120/2400		120	100	1.5	
EG-F-150/2400		150	150	1.5	
EG-F-200/2400		200	150	2.0	
EG-F-250/2400		250	200	2.0	
EG-F-300/2400		300	200	2.0	



FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

