PRODUCT DATASHEET



C3/4T

SUPPORT PLATE FOR PAVING



DESCRIPTION:

This product is manufactured in a weather-proof recycled material and consists of one piece. At 122mm diameter, the C3/4T support plate for paving is fitted on top of any adjustable base and keeps a constant 3mm gap between each slab/tile.

Colour: Black Weight: 38g per piece Height of upstands: 15mm Thickness of upstands: 3mm

LOAD/m2 INFORMATION:

FOR PAVING: FOR DECKING:

 600×600 mm slabs/tiles (2.25 pedestals/m2) – 1,350kg/m2 500×500 mm slabs/tiles (4.00 pedestals/m2) – 2,400kg/m2 400×400 mm slabs/tiles (6.25 pedestals/m2) – 3,750kg/m2 600mm centres/intervals (2.25 pedestals/m2) - 1,350kg/m2 500mm centres/intervals (4.00 pedestals/m2) - 2,400kg/m2 400mm centres/intervals (6.25 pedestals/m2) - 3,750kg/m2

THIS PRODUCT IS PREDOMINANTLY ORDERED WITH:

PV3.5/5 35-50mm high

PV5/8 50-80mm high



PV8/11 80-110mm high



PV11/14 110-140mm high



PV14/17 140-170mm high



OTHER ACCESSORIES AVAILABLE WITH THIS PRODUCT:

F30

Pedestal extension piece: 30mm high



PS₂

Rubber Packer Shim: 2mm thick



PACKAGING:

Sold in bags of 50 only Bag weight: 2kg

Full pallet of C3/4T would consist of 16 bags (4000 in total)

Pallet dimension: 1200 x 1100 x 1200mm

Total pallet weight: 170kg