PRODUCT DATASHEET



PV14/17

ADJUSTABLE BASE TO SUIT HEIGHTS: 140-170mm



DESCRIPTION:

This product is manufactured in a weather-proof recycled material and consists of two pieces. The bottom piece is 215mm in diameter and has eight vertical ribs. The top piece consists of the adjustable thread and eight further recesses for added reinforcement.

Colour: Black Support area: 300cm2 Weight: 300g per piece Temperature resistance: -25 to +70C


LOAD/m2 & PRESSURE TEST INFORMATION:

FOR PAVING:

600 x 600mm slabs/tiles (2.25 pedestals/m2) - 1,350kg/m2 500 x 500mm slabs/tiles (4.00 pedestals/m2) - 2,400kg/m2 400 x 400mm slabs/tiles (6.25 pedestals/m2) - 3,750kg/m2

FOR DECKING:

600mm centres/intervals (2.25 pedestals/m2) - 1,350kg/m2 500mm centres/intervals (4.00 pedestals/m2) - 2,400kg/m2 400mm centres/intervals (6.25 pedestals/m2) – 3,750kg/m2



THIS PRODUCT IS PREDOMINANTLY ORDERED WITH:

C3/4T

Support plate for paving



Support plate with no upstands



Pedestal extension piece: 30mm high

Support plate for decking



CPV

Support plate for > 75mm joists



OTHER ACCESSORIES AVAILABLE WITH THIS PRODUCT:

F30

AF100

Pedestal extension piece: 100mm high



HS2

2-degree Slope Corrector



PS₂


Rubber Packer Shim: 2mm thick



PACKAGING:

Sold in bags of 40 only Bag dimension: 1450 x 750mm

Bag weight: 13kg







Full pallet of PV14/17 would consist of 12 bags (480 in total)

Pallet dimension: 1200 x 1100 x 2000mm

Total pallet weight: 166kg