

PLATIPUS ROOTBALL FIXING SYSTEM PLATI-MAT

KIT INCLUDES



RF_P

Installation Tools

(Tools not included)



Drive Rod
(HDRS_ / PDRS_)



Plati-Hook (Optional)



Tension Lever (TL1 / TL2)

Key Benefits

- System starts to break down in 3-5 years
- Larger range of anchors for bigger range of trees
- Plati-Mat for rootball protection (stops wire cutting into roots)
- Use in undisturbed soil
- Anchors made from aluminium alloy
- Two way ratchet tensioner allows for even stability & pressure on the rootball
- Ideal for rootballed, airpot & containerised trees



TREE HEIGHT/ GIRTH	DESCRIPTION	PRODUCT CODE	TOOLS REQUIRED		
			DRIVE RODS	LOADLOCKING	TENSIONER
up to 2.5m up to 12cm	3 x S21 anchors, 2 metres of galvanised wire, 1 x ratchet tensioner & 3 x Plati-Mats.	RF0P	HDRS2	PH0	-
2.5 - 4.5m 12 - 25cm	3 x S41 anchors, 4 metres of galvanised wire, 1 x ratchet tensioner & 3 x Plati-Mats.	RF1P	HDRS4 / PDRS4 22x108 (22mm x 108mm)	PH1	TL1
4.5 - 7.5m 25 - 45cm	3 x S61 anchors, 5 metres of galvanised wire, 1 x ratchet tensioner & 3 x Plati-Mats.	RF2P	HDRS6 / PDRS6 22x108 (22mm x 108mm)	PH1	TL1
7.5 - 12m 45 - 75cm	3 x S81 anchors, 8 metres of galvanised wire, 1 x ratchet tensioner & 3 x Plati-Mats.	RF3P	HDRS8 / PDRS8 32x160 (32mm x 160mm)	BS12 (with Strop)	TL2
12m+ 75cm+	3 x B41 anchors, 10 metres of galvanised wire, 1 x ratchet tensioner & 3 x Plati-Mats.	RF4P	PDRS8 32x160 (32mm x 160mm)	BS12 (with Strop)	TL2

PDEA®, ARGs® and ARVS® are Registered Trademarks of Platipus Anchors.
Platipus Anchors technology is protected by International Patents, Trademarks and Registered Copyright.

PLATIPUS
TREE ANCHORING SYSTEMS
www.platipus-anchors.com

Platipus Anchors Limited,
Kingsfield Business Centre, Philanthropic Road,
REDHILL, Surrey, RH1 4DP, England.
T: +44 (0) 1737 762300
E: info@platipus-anchors.com

Platipus Anchors Inc,
1902 Garner Station Boulevard,
Raleigh, NC 27603, USA.
T: Toll Free (USA): (866) 752-8478 T: (919) 662-0991
E: trees@platipus.us

Notes: This arrangement is intended only as a guide. The designer and contractor should satisfy themselves as to the integrity of the design and make third party checks accordingly.